# Technical Data Sheet

Creation date : July 31, 2002
Latest change : 2 October 2013
Print date : 23 January 2014
Number of pages : 1

## General

Article number: 5420

Description: Colad Fine Dust Mask with Exhale Valve.



## Specification

| | |
|---|---|
| - Main component: | felt. |
| - Remarks: | with 2 elastic head bands,<br>with exhale valve,<br>with adjustable nose clip. |
| - Basic weight: | 130 g/m², fibre diameter 2-5 micrometer. |
| - Dust classification: | 2S (P2). |
| - Approval: | according to European Norm EN 149 FFP2S (Notified Body number 0086). |
| - CE-marking: | 0121. |
| - Packing: | 15 pieces in printed box. |
| - Packing unit: | 6 x 15 pieces per carton. |

## Remarks

- Protects against fine dust caused by sanding and grinding.
- The Colad Fine Dust Mask with Exhale Valve is light weight and has an adjustable nose clip for comfortable fit.
- The special exhale diaphragm breather valve permits easy escape of warmth and moisture ensuring maximal wearing comfort.
- It can protect against non toxic, low to the average toxicity solid en liquid aerosols (e.g. oil-mists) in concentrations up to 12 x OEL.
- With asbestos; please pay attention to the regulations concerned depending on the kind of work which requires more important safety preparations.
- Fine Dust Masks of this type do not protect the user against gas, vapours, solvents and liquid aerosols.
- Do not use the mask for more than 8 hours.

## Created by :

E.M.M. International BV
Marsweg 59
8013 PE Zwolle
The Netherlands

phone +31 38 4676600
fax +31 38 4676699
www.emm-automotive.com